

## Standard RTD Element

### Part number format:

Sample PN: SE-1000-L12-2

SE - 1000 - L12 - 2

└───┬───┬───┘  
A     B     C

Our complete list of sensors is listed below.



### Sensor Configuration:

SE Sensor Element

#### A

##### Birk PN/RTD Size

1000	100 ohm 2.3mm x 2mm x 1.3mm
1001	100 ohm 2.3mm x 2mm x 1.3mm
1002	100 ohm 1.6mm x 1.2mm x 0.8mm
1003	1000 ohm 5mm x 2mm x 1.3mm
1004	1000 ohm 1.6mm x 1.2mm x 0.8mm
1005	1000 ohm 5mm x 2mm x 1.3mm
1006	100 ohm 2mm x 2mm x 1.3mm
1007	100 ohm 3mm x 0.8mm x 0.6mm
1008	1000 ohm 3mm x 0.8mm x 0.6mm

#### B

##### Lead Length:

L12	12" length
L18	18" length
L24	24" length
L36	36" length

#### C

##### Number of Leads

2
3
4

### Birk Quality and Accuracy

Birk Sensors provide a cutting edge ability to more accurately measure the output of your application and convert the information to be used for observation. Each RTD from Birk's Sensor line meets the EN60751 Class B Industry tolerance.

All brand or product names are or may be trademarks of, and are used to identify products or services of, their respective owners. Item # PS-SE-B  
© 2014 Birk Manufacturing, Inc. [www.birkmfg.com](http://www.birkmfg.com) 14 Capitol Drive, East Lyme, CT 06333 860.739.4170