



Standard Sensor Ring Terminal

Part number format:

Sample PN: SRT-1000-L12-2

Our complete list of sensors is listed on the next page.

SRT - 1000 - L12 - 2
A B C



Sensor Configuration:

SRT –Sensor Ring Terminal

A

Birk PN/RTD Size

1000
1001
1002
1003
1004
1005

C

Number of Leads

2
3
4

B

Lead Length:

L12 - 12" length
L18 - 18" length
L24 - 24" length
L36 - 36" length

Birk Quality and Accuracy

Birk Sensors provide a cutting edge ability to more accurately measure the output of your application and convert the information to be used for observation. Each RTD from Birk's Sensor line meets the EN60751 Class B Industry tolerance.

All brand or product names are or may be trademarks of, and are used to identify products or services of, their respective owners. Item # PS-SRT-B
© 2014 Birk Manufacturing, Inc. www.birkmfg.com 14 Capitol Drive, East Lyme, CT 06333 860.739.4170



Standard Sensor Ring Terminal Selection Sheet

Sensor Configuration	BPN	Dimension			Leads			Temperature Range	Resistance
		Length (mm)	Width (mm)	Thickness (mm)	Material	Diameter	Length		
SRT	1000	2.3	2	1.3	Silver (Ag)	0.25	10	-200C to 400C	100 ohms @ 0C
SRT	1001	2.3	2	1.3	Platinum/Nickel	0.2	10	-200C to 600C	100 ohms @ 0C
SRT	1002	1.6	1.2	0.8	Silver (Ag)	0.25	10	-200C to 400C	100 ohms @ 0C
SRT	1003	5	2	1.3	Platinum/Nickel	0.2	10	-200C to 600C	1000 ohms @ 0C
SRT	1004	1.6	1.2	0.8	Silver (Ag)	0.25	10	-200C to 400C	1000 ohms @ 0C
SRT	1005	5	2	1.3	Silver (Ag)	0.25	10	-200C to 400C	1000 ohms @ 0C